

Indian Valley Industries, Inc.

Technical Data Sheet

IVI 3611MB - AASHTO Silt Fence- NYSDOT Approved

3' x 100' with Mesh - 10' Stake Spacing
1.25" x 1.25" x 48" Pointed Hardwood Stakes

This is to certify that IVI 3611MB NYSDOT Silt Fence Fabric, a woven polypropylene fabric will meet or exceed the following typical values when tested in accordance with the proper ASTM method. Complies to AASHTO specification M-288.

PRODUCT TEST DATA		
Physical Property	Test Method	Typical Value
Composition		Polypropylene
Construction		20 x 9.3
Color	Belton Industries, Inc. - Style #940	Black
Tensile Strength - Warp	ASTM D-4632	150 lbs
Tensile Strength - Fill	ASTM D-4632	125 lbs
Elongation - Warp	ASTM D-4632	20%
Elongation - Fill	ASTM D-4632	15%
Trapezoidal Tear - Warp	ASTM D-4533	70 lbs
Trapezoidal Tear - Fill	ASTM D-4533	70 lbs
Puncture Strength	ASTM D-4833	90 lbs
Apparent Opening Size	ASTM D-4751	.425mm
Permittivity	ASTM D-4491	0.250 Sec-1
U.V. Resistance % Retained (500 hrs)	ASTM D-4355	80%

Test results represent Minimum Average Roll Values (MARV) with the exception of weight which is a typical result.

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.